



**PRODUCT NUMBER: R60X**  
**Redcote Plus - R60X**

Handling in an aggressive environment: oils, greases, chemicals, hydrocarbons. Chemical and petrochemical industry.

**Honeywell**

## Overview

**Reference Number**

R60X

**Product Type**

Gloves

**Range**

Chemical Protection

**Line**

Heavy chemical

**Brand**

Honeywell

**Brand formerly known as**

NORTH

**Industry**

- Agriculture
- Chemical Industries
- Petro-chemical
- Water treatment

**Product Use**

Handling in an aggressive environment: oils, greases, chemicals, hydrocarbons. Chemical and petrochemical industry.

## Features & Benefits

**Feature**

Red PVC glove Dipped on cotton liner Smooth finish

**Benefit**

**COMFORT** The cotton interlock lining absorbs hand perspiration for added comfort. Its smooth finish offers an excellent touch and increases dexterity. The glove's articulated fingers offer superior comfort and reduce effort in cases extended use. **RESISTANCE** Its PVC composition has been tailored for multi-purpose and repetitive handling in an oily atmosphere. The cotton interlock lining strengthens the glove's mechanical performance. Low resistance to ketones, aromatic and halogen hydrocarbons. **SAFETY** As a result of its superior quality PVC and being part of PPE Class III, it ensures excellent follow-up on quality. The cuff helps to protect a large part of the forearm. **HYGIENE** Sanitized treatment

## Technical Description

### Description

Red PVC glove Dipped on cotton liner Smooth finish

### Product Technology

Dipped

### Glove/liner color

Red

### Coating Type

PVC

### Length

40 cm

### Thickness

1,4 mm

### Harmlessness

In conformity with the European standards.

### Dexterity

Class 5

### Sizes

9L, 10XL

## EN 388 - Mechanical Hazards Abrasion Resistance

|                                 |   |
|---------------------------------|---|
| Abrasion resistance             | 4 |
| Cutting resistance (Coupe test) | 1 |
| Tear resistance                 | 2 |
| Puncture resistance             | 1 |

## EN 374-3 Resistance to

|                                       |     |
|---------------------------------------|-----|
| Resistance to permeation by chemicals | AKL |
|---------------------------------------|-----|

## Packaging Label

### Tagging

CE0075 Honeywell R60X XX EN 420 EN 388 : 4121 EN 374-3 : AKL

## Certifications

### E.C. Declaration of Conformity

#### EC Category PPE

3

#### EC Certificate Number

0075/797/162/05/13/0457 EXT 02/05/13

#### EC Attestation

 EC Attestation

#### EC Attestation Number

0075/797/162/05/13/0457 EXT 02/05/13

#### Certifications

- EN 0075/797/162/05/13/0457 EXT 02/05/13

## Additional Information

**User Manual**

UI 104

## Maintenance

**Storage Information**

Minimum packaging : 12 pairs Cartons of 48 pairs.

**Care Instructions**

In order to keep its properties, this article should not be cleaned.

© Honeywell International Inc.